



## Safety Data Sheet

Dynaflux SDS WM305A 01/17/2017

Product: Weldmark Spray Galv Bright WM305-16

**Part 1: Product and Company Identification**

Identification 305A

Trade Name: Weldmark Spray Galv Bright WM305-16

Product Use: Sacrificial protection that stops rust and corrosion.

Manufacturers Name: Dynaflux, Inc.

241 Brown Farm Rd.

Cartersville, GA 30120 U.S.A.

Manufactured for: I.W.D.C. , 6331 East 30<sup>th</sup> St. # 301 Indianapolis, IN 46219

Emergency Telephone Number: For U.S.: 800-255-3924 International: 813-248-0585

**Part 2: Hazardous Ingredients**

6

Signal Word: **WARNING****H229:** Pressurized container: may burst if heated**H351:** Suspected of causing cancer

Hazardous Ingredients	CAS No.	SARA III List	PEL PPM	TLV PPM	Carcinogen Refer. Source
Dichloromethane	75-09-2	Yes	25	12.5	IARC NTP
Propane	74-98-6	Yes	1000	1000	d
Zinc Dust & resin binder	7440-66-6	No	200	200	d

**Part 3: Hazard Rating****H.M.I.S.**

Health	2
Flammability	2
Reactivity	0
Special	0

**N.F.P.A.**

Health	2
Flammability	2
Reactivity	0
Personal Protection	b

**Part 4: First Aid Measures**Eye Contact: Flush with water for 15 minutes. If irritation persists call a physician. **GHS: Category 2A**Skin Contact: Flush with water. Wash with soap and water. Apply a lotion. **GHS: Category 2**

Inhalation: Move to fresh air.

Ingestion: Do not induce vomiting. Give several large glasses of water. Seek medical attention. **GHS: Category 4****Reproductive Toxicity: GHS Category 2****Carcinogenicity: GHS Category 2**

**Part 5: Fire Fighting Measures**

Flashpoint: Nonflammable Flame Projection Test

U.E.L.: None Established

L.E.L. : None Established

Auto Ignition Temperature: 662°C.

Combustion Products: Carbon dioxide, carbon monoxide, hydrogen chloride and small amounts of phosgene.

Extinguishing Media: Foam, CO<sub>2</sub>, Dry chemical

Unusual Fire and Explosion Hazard: use a self contained breathing apparatus. Use water fog to cool containers to prevent rupturing.

**Part 6: Accidental Release Measures**

Small Spill: Soak up with absorbent material, i.e. kitty litter, clay or dirt. Sweep up and place in a labeled closed container.

Large Spill: Keep unauthorized people from the area. Use self contained breathing apparatus. Dike area and pump contents to a labeled, closed container. Absorb residue and sweep up. Place in a closed, labeled container.

**Part 7: Handling and Storage**

Leave in the shipping containers. Store in a cool dry place. Do not expose aerosols to temperatures above 120° F or the container may rupture.

**Part 8: Exposure Control / Personal Protection**

If vapor exceeds TLV use a approved respirator. Use mechanical ventilation in confined spaces. Wear safety glasses and protective gloves.

**Part 9: Physical and Chemical Properties**

Boiling Point: NA

Vapor Pressure : 47.33 KPa

Vapor Density: NE

Appearance and Odor: Silver; chlorinated solvent odor

Evaporation Rate (BuAc=1): >1

Water Reactive: No

**Part 10: Stability and Reactivity**

Stability- Product is stable

Hazardous Polymerization- will not occur.

Conditions to Avoid- Ignition sources, open flames, amines and strong bases.

**Part 11: Toxicological Information**

Ingestion: Rat LD<sub>50</sub> 1500-2500mg/kg

Inhalation: Rat LC<sub>50</sub> 10,000 ppm

Carcinogenicity Classification: N.T.P. Anticipated Carcinogen. IARC: Possible carcinogen; 2B

Reproductive Toxicity: animal studies- None

Genetic Toxicity-negative results from animal studies.

Continued

**Part 12: Ecological Information**

Potential for mobility in soil is high.  
Octanol/Water partition coefficient: 1.25  
Organic carbon/water partition coefficient: 24  
Atmospheric half life: 79-110 days  
Biodegradation 5-26% 28 days  
Aquatic Toxicity EC50 water flea. Immobilization: 480 mg/l

**Part 13: Disposal Consideration**

Do not dump into any sewers, on the ground or into any body of water. Send to a permitted recycler.

**Part 14: Transportation Information****DOT HM-181 Shipping Information**

D.O.T. Shipping Name – Consumer Commodity  
Hazard Class or Division: ORM-D  
UN Number: 1950  
Packing Group: III  
Label(s) Required: None

**TDG Shipping Information**

TDG Shipping Name: Aerosols, Nonflammable  
Hazard Class: 2.2  
Sub classification : 6.1  
UN Number: 1950  
Packing Group: None  
Label(s) Required: Non-flammable Gas

**Part 15: Regulatory Information**

Section 311 and 312  
Immediate Health Hazard – Yes  
Delayed Health Hazard- Yes  
Fire Hazard – No  
Reactive Hazard – No  
Section 313- Dichloromethane  
TSCA – The product on this MSDS, or all of its components, is listed under TSCA.  
CEPA-(DSL) Listed

**Part 16: Other Information**

Dynaflux, Inc.  
241 Brown Farm Rd.  
Cartersville, GA 30120 U.S.A.

**Disclaimer of Expressed and implied Warranties:**

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date of the Safety Data sheet was prepared. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices as specified on the label copy.